

MODEL				ASH-09BIS2/W, ASH-09BIS2/B							
FUNCTION				FUNCTION							
Cooling	Yes		Average season	Yes							
Heating	Yes		Warmer season	Yes							
			Colder season	Yes							
Design load			Seasonal efficiency								
Item	symbol	value	unit	Item	symbol	value	unit				
Cooling	Pdesignc	2,7	kW	Cooling	SEER	8,5	--				
Heating / Average	Pdesignh	3,5	kW	Heating / Average	SCOP/A	5,1	--				
Heating / Warmer	Pdesignh	3,8	kW	Heating / Warmer	SCOP/W	5,7	--				
Heating / Colder	Pdesignh	4,8	kW	Heating / Colder	SCOP/C	3,8	--				
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj							
Item	symbol	value	unit	Item	symbol	value	unit				
Tj = 35 °C	Pdc	2,73	kW	Tj = 35 °C	EERd	5,34	--				
Tj = 30 °C	Pdc	2,09	kW	Tj = 30 °C	EERd	7,89	--				
Tj = 25 °C	Pdc	1,23	kW	Tj = 25 °C	EERd	11,80	--				
Tj = 20 °C	Pdc	1,19	kW	Tj = 20 °C	EERd	16,37	--				
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Average season, at indoor temperature 20 °C and outdoor temperature Tj							
Item	symbol	value	unit	Item	symbol	value	unit				
Tj = - 7 °C	Pdh	3,10	kW	Tj = - 7 °C	COPd	3,31	--				
Tj = 2 °C	Pdh	1,89	kW	Tj = 2 °C	COPd	5,12	--				
Tj = 7 °C	Pdh	1,26	kW	Tj = 7 °C	COPd	6,33	--				
Tj = 12 °C	Pdh	0,80	kW	Tj = 12 °C	COPd	7,35	--				
Tj = bivalent temperature	Pdh	3,60	kW	Tj = bivalent temperature	COPd	2,85	--				
Tj = operating limit	Pdh	3,10	kW	Tj = operating limit	COPd	3,31	--				
Declared capacity for heating / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj							
Item	symbol	value	unit	Item	symbol	value	unit				
Tj = 2 °C	Pdh	3,89	kW	Tj = 2 °C	COPd	3,38	--				
Tj = 7 °C	Pdh	2,45	kW	Tj = 7 °C	COPd	5,45	--				
Tj = 12 °C	Pdh	1,09	kW	Tj = 12 °C	COPd	6,53	--				
Tj = bivalent temperature	Pdh	3,89	kW	Tj = bivalent temperature	COPd	3,38	--				
Tj = operating limit	Pdh	3,89	kW	Tj = operating limit	COPd	3,38	--				
Declared capacity for heating / Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Colder season, at indoor temperature 20 °C and outdoor temperature Tj							
Item	symbol	value	unit	Item	symbol	value	unit				
Tj = - 7 °C	Pdh	2,95	kW	Tj = - 7 °C	COPd	3,12	--				
Tj = 2 °C	Pdh	1,78	kW	Tj = 2 °C	COPd	4,87	--				
Tj = 7 °C	Pdh	1,15	kW	Tj = 7 °C	COPd	5,25	--				
Tj = 12 °C	Pdh	0,73	kW	Tj = 12 °C	COPd	6,65	--				
Tj = operating limit	Pdh	3,90	kW	Tj = operating limit	COPd	2,11	--				
Tj = bivalent temperature	Pdh	4,11	kW	Tj = bivalent temperature	COPd	2,12	--				
Tj = - 15 °C	Pdh	4,11	kW	Tj = - 15 °C	COPd	2,12	--				
Bivalent temperature				Operating limit temperature							
Item	symbol	value	unit	Item	symbol	value	unit				
Heating / Average	Tbiv	-7	°C	Heating / Average	Tol	-10	°C				
Heating / Warmer	Tbiv	2	°C	Heating / Warmer	Tol	2	°C				
Heating / Colder	Tbiv	-15	°C	Heating / Colder	Tol	-30	°C				
Cycling interval capacity				Cycling interval efficiency							
Item	symbol	value	unit	Item	symbol	value	unit				
For cooling	Pcycc	x,x	kW	For cooling	EERcyc	x,x	--				
For heating	Pcych	x,x	kW	For heating	COPcyc	x,x	--				
Degradation co-efficient cooling	Cdc	0,25	--	Degradation co-efficient heating	Cdh	0,25	--				
Electric power input in power modes other than 'active mode'				Annual electricity consumption							
Off mode	P <sub>OFF</sub>	0,0048	kW	Cooling	Q <sub>CE</sub>	111	kWh/a				
Standby mode	P <sub>SB</sub>	0,0048	kW	Heating / Average	Q <sub>HE</sub>	961	kWh/a				
Thermostat-off mode	P <sub>TO</sub>	0,0051/0,00913	kW	Heating / Warmer	Q <sub>HE</sub>	933	kWh/a				
Crankcase heater mode	P <sub>CK</sub>	0,000	kW	Heating / Colder	Q <sub>HE</sub>	2653	kWh/a				
Capacity control				Other items	symbol	value	unit				
Fixed	No		Sound power level (indoor/outdoor)	L <sub>WA</sub>	58/62	dB(A)					
Staged	No		Global warming potential	GWP	675	kgCO <sub>2</sub> eq.					
Variable	Yes		Rated air flow (indoor/outdoor)	--	800/2400	m <sup>3</sup> / h					
Name and address of the manufacturer or of its authorised representative.				Manufacturer: SINCLAIR Corp. Ltd., 1-4 Argyll St., London, UK Representative: SINCLAIR EUROPE spol. s r.o., Purkynova 45, 612 00 Brno, CZ							
Contact details for obtaining more information				info@sinclair-solutions.com / www.sinclair-solutions.com							

\* R32 (100% HFC-32)

\* Device contains fluorinated greenhouse gases covered by the Kyoto Protocol.